


## QL Neva



Explosie veilig IP66, IK08 LED armatuur met transparante polycarbonaat afscherming. Glasvezelversterkte behuizing (polyester) in geel (RAL1003) met RVS clips voor sluiting. Binnenreflector uit wit gelakt plaatstaal.

Geschikt voor zone 2 en 22. Volgens ATEX normering 2014/34/EU. Ex nA IIC T6 Gc en Ex t IIIC T85C Dc. Armatuur rendement >100lm/w.

Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80). Ta -25°C / +40°C. Vijf jaar garantie.

Explosion proof IP66, IK08 LED luminaire with transparant polycarbonate diffuser. Glass fibre reinforced polyester housing in yellow (RAL1003) with stainless steel clips. White laquered steel plate gear tray.

Suitable for zone 2 and 22. According ATEX directive 2014/34/EU. Ex nA IIC T6 Gc en Ex t IIIC T85C Dc. Fixture efficiency >100lm/w.

Maintenance free and long lifetime (50.000 hours L80). Ta -20°C / +40°C. Five year warranty.

Vermogen Power	Kleur Colour	Lumen	CRI (Ra)	Lengte (mm) Length (mm)	Breedte (mm) Width (mm)	Hoogte (mm) Height (mm)	Clips	Ta,Max Ta,Max	kg	Noodvoorz. (h) Emergency (h)	Art. nummer Article no.
22w	4000k	2200	>80	665	145	101	6	40	2	-	OA02223040
40w	4000k	4400	>80	1282	145	101	6	40	3,25	3 (340lm)	OA04023040
45w	4000k	5200	>80	1578	145	101	8	40	3,60	3 (330lm)	OA04523040

### Accessoires:

- RVS ophangbeugel

### Opties:


- Noodverlichting 3 uur (1200 en 1500mm)
- Polyamide of messing vernikkelde ATEX kabel wartel

### Accessories:

- Stainless steel clips

### Optional:

- 3 hour emergency (1200 and 1500mm)
- Polyamide or brass nickel plated ATEX cable gland



OA04523040  
45w 5200lm 4000k  
ηLB 100%

