




QL Albireo

Ronde LED downlight met een lage inbouwhoogte. Voorzien van trompetvormige darklight reflector van 99,98% hoogglans aluminium met brede bundel (> 77°). Zeer lage verblinding (UGR < 18) en minimale helderheid door uniek darklight reflector ontwerp. Wit gelakte (RAL 9003) aluminium behuizing. Wordt geleverd inclusief externe driver. Voorzien van 0,5m kabel met GST18i3 connector (male). Voor 1-10v en Dali extra kabel met BST14i2 connector (male). Directe aansluiting op netspanning. Snelle en eenvoudige montage met veren. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80). Kleur stabiliteit, MacAdam <3. Vijf jaar garantie.

Round LED downlight with shallow build-in height. Trumpet shaped darklight reflector made of 99,98% specular aluminium with wide beam angle (> 77°). Very low glare (UGR < 18) and minimal brightness due to unique darklight reflector design. White painted die cast aluminium body (RAL9003). Standard supplied with 0,5m cable with GST18i3 connector (male). For 1-10V and Dali extra cable with BST14i2 connector (male). Direct connection to mains. Low maintenance and long life expectancy (50.000 hours L80). Color stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.



Vermogen Wattage	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali
9w	3000k	1135	250	1,3	1/3	MM00923030	MM00923031	MM00923032
13w	3000k	1515	350	1,3	1/3	MM01323030	MM01323031	MM01323032
18w	3000k	2060	500	1,3	1/3	MM01823030	MM01823031	MM01823032
25w	3000k	2965	700	1,3	1/3	MM02523030	MM02523031	MM02523032
33w	3000k	3615	900	1,3	1/3	MM03323030	MM03323031	MM03323032
40w	3000k	4035	1050	1,3	1/3	MM04023030	MM04023031	MM04023032
9w	4000k	1165	250	1,3	1/3	MM00923040	MM00923041	MM00923042
13w	4000k	1555	350	1,3	1/3	MM01323040	MM01323041	MM01323042
18w	4000k	2125	500	1,3	1/3	MM01823040	MM01823041	MM01823042
25w	4000k	3070	700	1,3	1/3	MM02523040	MM02523041	MM02523042
33w	4000k	3740	900	1,3	1/3	MM03323040	MM03323041	MM03323042
40w	4000k	4160	1050	1,3	1/3	MM04023040	MM04023041	MM04023042

*Lichtstroom van armatuur, tolerantie van +/- 10%

*Luminaire luminous flux, tolerance of +/- 10%

Accessoires:

- GST18i3 splitter
- BST14i2 splitter blauw

Accessories:


- GST18i3 splitter
- BST14i2 splitter blue

Opties:

- Wago Winsta connectoren
- 2700K, 3500K of 5000K op aanvraag
- Micro prisma comfort afscherming (max. -3 UGR)
- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

Options:

- Wago Winsta connectors
- 2700K, 3500K or 5000K available on request
- Micro prismatic comfort diffuser (max. -3 UGR)
- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI



MM01323040
13w 4000k 1850lm
ηLB 84,0%

