




QL Biham

Extrem laag inbouw LED downlight (26mm) met wit gelakte aluminium behuizing (RAL 9010). Zeer hoge kwaliteit LED's met hoge kleurweergave (>90 CRI). Speciale combinatie PMMA diffusers voor egale lichtverdeling met 115° uitstralingshoek. Standaard verkrijgbaar in warm wit (3000k) en neutraal wit (4000k). Zeer goed toepasbaar in hallen, trappenhuisen en ruimtes met weinig inbouw ruimte. Wordt geleverd inclusief externe driver. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L70). Kleur stabiliteit, MacAdam <3. Vijf jaar garantie.

Extremely shallow recessed LED downlight (26mm) white painted aluminium housing (RAL 9010). Very high quality LEDs with high colour rendering (CRI>90). Due to a special combination of PMMA diffusers the light distributions is uniform and has a 115° beam angle. Standard available in warm white (3000k) and neutral white (4000k). Very suitable in toilets, corridors, stairways and rooms with limited build-in height. Delivered including external driver. Direct connection to mains. Low maintenance and long life expectancy (50.000 hours L70). Color stability, MacAdam <3. Fast and easy mounting with springs. Five years warranty.



Vermogen Wattage	Kleur Colour	Diameter (mm) Diameter (mm)	Zaagmaat Cutsize	Lumen* Lumen*	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Artikelnr. Article number	Dimbaar (1-10v) Dimmable (1-10v)	Dali
5	3000k	121	108	420	150	0,3	MV00523030	MV00523031	MV00523032
8	3000k	121	108	650	350	0,3	MV00823030	MV00823031	MV00823032
9	3000k	173	160	680	250	0,5	MV00923030	MV00923031	MV00923032
13	3000k	173	160	900	350	0,5	MV01323030	MV01323031	MV01323032
12	3000k	224	210	1000	500	0,8	MV01223030	MV01223031	MV01223032
18	3000k	224	210	1450	700	0,8	MV01823030	MV01823031	MV01823032
18	3000k	270	260	1450	700	1,2	MV01923030	MV01923031	MV01923032
23	3000k	270	260	1775	900	1,2	MV02323030	MV02323031	MV02323032
5	4000k	121	108	465	150	0,3	MV00523040	MV00523041	MV00523042
8	4000k	121	108	715	350	0,3	MV00823040	MV00823041	MV00823042
9	4000k	173	160	800	250	0,5	MV00923040	MV00923041	MV00923042
13	4000k	173	160	1065	350	0,5	MV01323040	MV01323041	MV01323042
12	4000k	224	210	1175	500	0,8	MV01223040	MV01223041	MV01223042
18	4000k	224	210	1560	700	0,8	MV01823040	MV01823041	MV01823042
18	4000k	270	260	1585	700	1,2	MV01923040	MV01923041	MV01923042
23	4000k	270	260	1935	900	1,2	MV02323040	MV02323041	MV02323042

*Lichtstroom van armatuur, tolerantie van +/- 10%

*Luminaire luminous flux, tolerance of +/- 10%

Accessoires:

- Gemonteerde 1,5 meter snoer + stekker (2-polig)
- Gemonteerde 0,5 meter snoer + GST18i3 male
- Gemonteerde 2x0,5 meter snoer + GST18i3 male + BST14i2

Accessories:


- Assembled 1,5 meter cable + plug (2-pole)
- Assembled 0,5 meter cable + GST18i3 male
- Assembled 2x0,5 meter cable + GST18i3 male + BST14i2

Opties:

- 2700k of 6000k op aanvraag

Options:

- 2700k or 6000k available on request



MV02323030
23W LED 1775lm
ηLB 100%

